


# CASSIDA PASTE AP

## Product Information

Synthetic assembly paste for food and beverage processing equipment



**CASSIDA PASTE AP** is specially developed for the maintenance of machinery in the food and beverage processing and packaging industry.

It is based on synthetic fluids and selected additives chosen for their ability to meet the stringent requirements of the food and beverage industry.

Registered by NSF (Class H1) for use where there is potential for incidental food contact. Produced according to FLT Quality Standards, in facilities where HACCP audit and Good Manufacturing Practice have been implemented and form part of the quality and hygiene management systems ISO 9001 and ISO 21469.

### CERTIFICATIONS AND SPECIFICATIONS

- NSF H1
- Kosher
- Halal



## PERFORMANCE FEATURES

- Easier disassembly after long periods of use
- Prevents cold welding on screw connections
- Excellent water resistance, hence suitable for friction points subjected to humidity
- Excellent resistance against acid and brine
- Prevents fretting corrosion
- Effective corrosion protection
- Good adhesive properties
- Neutral odour and taste

## APPLICATIONS

- Assembly paste with an extremely large range of applications
- Screw paste for high-alloy steels to optimize the tightening torque
- Mounting and pressing of bearings and disks, wheels and bolts
- Lubrication of adjusting mechanisms as well as for drifting, bending, punching, pressing and stamping.

## OPERATING TEMPERATURES

-40 °C to +1200 °C

## SEAL AND PAINT COMPATIBILITY


Compatible with the elastomers, gaskets, seals and paints normally used in food machinery lubrication systems.

## HANDLING AND STORAGE

All food grade lubricants should be stored separately from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 0 °C and +40 °C. Provided that the product has been stored under these conditions we recommend that the product be used within 3 years from the date of manufacture. Upon opening a pack, the product must be used within 2 years (or within 3 years of date of manufacture, whichever is the sooner).

## TYPICAL CHARACTERISTICS (Typical for current production. Variations in these characteristics may occur.)

		<b>CASSIDA PASTE AP</b>	
<b>Property</b>		<b>Test Method</b>	
NSF Reg. No.			144807
Appearance			White smooth paste
Worked penetration at +25 °C	1/10 mm	ISO 2137	300 - 330



**FUCHS LUBRITECH GMBH**  
Werner-Heisenberg-Straße 1  
67661 Kaiserslautern / Germany  
T: +49 (0) 6301 3206-0 / F: +49 (0) 6301 3206-940  
www.fuchs-lubritech.com

 A Member of the  
FUCHS PETROLUB Group

As far as we know these information reflect the current state of knowledge and our research. They cannot, however, be taken as an assurance about the properties nor as a guarantee of the suitability of the product for the individual case in point. Before using our products the purchaser must, therefore, check the suitability and be satisfied that the output will be satisfactory. Our products are continually being up-dated. We reserve the right, therefore, to alter the information of this product information at any time and without prior announcement. We are specialized in developing products for extreme tribological problems in cooperation with end users. FUCHS LUBRITECH provides service and individual advice. Please contact us!  
E-Mail: cassida.lubricants@fuchs-lubritech.de